


SUBMITTAL DATA FLOW DIVERTER

FD SERIES CLASS 250/300



MAXIMUM OPERATING CONDITIONS	
Working Temperature	250 Deg F
Working Pressure	300 PSI

MATERIALS OF CONSTRUCTION	
Body	Steel
Strainer	Stainless Steel

MODEL	SYSTEM CONN.	PUMP CONN.	DIMENSIONS					
			A	B	C	D	E	F
1.5 X 1.5	1.5"	1.5"	7.13"	7.88"	7.13"	12.88"	13.06"	5.93"
2 X 1.25		1.25"						
2 X 1.5	2"	1.5"						
2 X 2		2"						
2.5 X 1.5	2.5"	1.5"						
2.5 X 2		2"						
2.5 X 2.5		2.5"						
3 X 1.5	3"	1.5"						
3 X 2		2"						
3 X 2.5		2.5"						
3 X 3		3"						
4 X 1.5	4"	1.5"						
4 X 2		2"						
4 X 2.5		2.5"						
4 X 3		3"						
4 X 4		4"						
5 X 2.5	5"	2.5"						
5 X 3		3"						
5 X 4		4"						
5 X 5		5"						
6 X 2.5	6"	2.5"						
6 X 3		3"						
6 X 4		4"						
6 X 5		5"						
6 X 6		6"						
8 X 4	8"	4"						
8 X 5		5"						
8 X 6		6"						
8 X 8		8"						
10 X 6	10"	6"						
10 X 8		8"						
10 X 10		10"						
12 X 8	12"	8"	CONSULT FACTORY					
12 X 10		10"						
12 X 12		12"						
14 X 10	14"	10"	17.00"	18.00"	23.06"	32.00"	32.19"	15.19"
14 X 12		12"						
14 X 14		14"						
16 X 10	16"	10"	CONSULT FACTORY					
16 X 12		12"						
16 X 14		14"						

JOB NAME _____
 LOCATION _____

 CONTRACTOR _____
 CONTRACTOR P.O. NO. _____

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____