

WBF Large Series ASME Bottom Feed Expansion Tank Full Acceptance

Features:

- Constructed in accordance with ASME Section VIII, Division I, Latest Edition
- Heavy Duty Butyl Bladder - NSF 61 Approved - Field Replaceable
- Fully Adjustable Field Air Charging
- Factory Air Charged to 12 P.S.I.
- Primed Exterior

Optional Features:

- Trimmed for Potable Water
- "Bulls Eye" sight glass
- Seismic mounting (clips or legs)
- EPDM Bladder Material
- Higher pressures available upon request. Tank dimensions will not change
- Painted Exterior, Epoxy Coatings



Dimensions are subject to change without notice,
Please confirm actual dimensions with factory at time of order.

Standard design pressure 125 PSI
Maximum design temperature 240°F with Butyl Bladder

PART NUMBER	ACCEPTANCE VOLUME	DIAMETER A (IN.)	HEIGHT B (IN.)	SYSTEM CONNECT (IN.)	WEIGHT (LBS)	WORKING PRESSURE
WBF2500	660	48"	94"	3"	2000	125 PSI
WBF3000	792	54"	86"	3"	2400	125 PSI
WBF4000	1050	54"	132"	3"	3200	125 PSI
WBF5000	1320	60"	110"	3"	3600	125 PSI
WBF6000	1590	60"	140"	3"	4000	125 PSI
WBF7500	1980	60"	174"	3"	4500	125 PSI
WBF8000	2100	72"	134"	3"	4600	125 PSI
WBF10000	2640	72"	159"	3"	4845	125 PSI

JOB NAME _____
 LOCATION _____

 CONTRACTOR _____
 CONTRACTOR P.O. NO. _____

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____

American WHEATLEY
HVAC PRODUCTS®
A GFP COMPANY

1005 E. Houston
Broken Arrow, OK 74012
Toll Free: 866-204-5229
PH: 918-317-0401
FAX: 918-317-0407
www.wheatleyhvac.com
e-mail: sales@globalflowproducts.com