


Liquid Level Sight Glass Assembly



WSG Series – Standard Pattern

Features:

- Rough brass water gauge
- 1/2" pipe size
- 5/8" O.D. glass
- 1/4" needle
- 1/4" needle drain valve in lower arm—standard
- Service rating of 125 psi at 350°F
- 1/4" pet cock in lower arm available upon request
- 1/4" ball valve in lower arm available upon request

Dimensions are subject to change without notice, please confirm actual dimensions with factory at time of order.

Dimensions:

Model	Glass O.D. x Length	Weight (lbs.)	Wheel Type
WSG08	5/8" X 8"	1	Composition
WSG10	5/8" X 10"	1	Composition
WSG12	5/8" X 12"	1 1/2	Composition
WSG16	5/8" X 16"	1 3/4	Composition
WSG20	5/8" X 20"	2	Composition
WSG22	5/8" X 22"	2	Composition
WSG28	5/8" X 28"	2	Composition

Dimensions are subject to change without notice, please confirm actual dimensions with factory at time of order.

JOB NAME _____
 LOCATION _____

 CONTRACTOR _____
 CONTRACTOR P.O. NO. _____

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____



1005 E. Houston
 Broken Arrow, OK 74012
 Toll Free: 866-204-5229
 PH: 918-317-0401
 FAX: 918-317-0407
 www.wheatleyhvac.com
 e-mail: sales@globalflowproducts.com