

Pneumatic Automated Butterfly Valves

American Wheatley offers pneumatic actuated butterfly valves with many available options. Please consult factory for price and availability.

- Double Acting
- Spring Return/Fail Safe
- Available 2" through 12:
- EPDM seats standard, Buna, PTFE and Viton available special request
- Powder coated aluminum body for severe duty applications
- Stainless steel fasteners
- ISO 5211 mounting standard
- All packages are supplied either direct mount or with a standard carbon steel bracket and coupler. Stainless steel bracket and coupler are available on request.



| JOB NAME _____ LOCATION _____ _____ _____ CONTRACTOR _____ CONTRACTOR P.O. NO. _____ | <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%; text-align: center;">ITEMS</th> <th style="width: 50%; text-align: center;">QUANTITY</th> </tr> </thead> <tbody> <tr><td>_____</td><td>_____</td></tr> <tr><td>_____</td><td>_____</td></tr> <tr><td>_____</td><td>_____</td></tr> <tr><td>_____</td><td>_____</td></tr> <tr><td>_____</td><td>_____</td></tr> <tr><td>_____</td><td>_____</td></tr> </tbody> </table> | ITEMS | QUANTITY | _____ | _____ | _____ | _____ | _____ | _____ | _____ | _____ | _____ | _____ | _____ | _____ | <p style="text-align: center;">American WHEATLEY HVAC PRODUCTS®</p> <p style="text-align: center;">1005 E. Houston Broken Arrow, OK 74012 Toll Free: 866-204-5229 PH: 918-317-0401 FAX: 918-317-0407 www.wheatleyhvac.com e-mail: sales@globalflowproducts.com</p> |
|---|--|-------|----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|---|
| ITEMS | QUANTITY | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |
| _____ | _____ | | | | | | | | | | | | | | | |

Double Acting

Available 2" through 12"

Available either configured double acting, for on/off service or with 4-20mA control or 3-15psi for modulating service

Optional manual override available on most sizes

Spring Return

Available 2" through 12"

Spring return actuators are fail-safe, ON/OFF, not available for control type applications.

Accessories

SVB 4 or 4 way solenoid valves

PosiCon+ limit switch

4-20mA I/P or 3-15psi P/P positioned

PNEUMATIC DOUBLE ACTING BASED ON 80 PSI

| Size | Lug Style | Wafer Style |
|------|-----------|-------------|
| 2 | BFL02DA15 | BFW02DA15 |
| 2.5 | BFL25DA20 | BFW25DA20 |
| 3 | BFL03DA20 | BFW03DA20 |
| 4 | BFL04SR25 | BFW04SR25 |
| 5 | BFL05SR25 | BFW05SR25 |
| 6 | BFL06SR30 | BFW06SR30 |
| 8 | BFL08SR30 | BFW10SR35 |
| 10 | BFL10SR35 | BWL10SR35 |
| 12 | BFL12SR40 | BFW12SR40 |

PNEUMATIC SPRING ACTING BASED ON 80 PSI

| Size | Lug Style | Wafer Style |
|------|-----------|-------------|
| 2 | BFL02SR15 | BFW02SR15 |
| 2.5 | BFL25SR20 | BFW25SR20 |
| 3 | BFL03SR20 | BFW03SR20 |
| 4 | BFL04DA25 | BFW04DA25 |
| 5 | BFL05DA25 | BFW05DA25 |
| 6 | BFL06DA30 | BFW06DA30 |
| 8 | BFL08DA30 | BFW10DA35 |
| 10 | BFL10DA35 | BWL10DA35 |
| 12 | BFL12DA40 | BFW12DA40 |

| |
|---------------------------|
| JOB NAME _____ |
| LOCATION _____ |
| _____ |
| CONTRACTOR _____ |
| CONTRACTOR P.O. NO. _____ |

| ITEMS | QUANTITY |
|-------|----------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |