

ELECTRIC AUTOMATED BUTTERFLY VALVES

American Wheatley offers electric actuated butterfly valves with many available options.

- Available 2” through 12”
- EPDM seats standard, Buna, PTFE and Viton available special request
- Voltages available: 115/60/1, 230/60/3
- Double acting or spring return models available
- NEMA 4
- Powder coated aluminum body for severe duty applications
- Stainless steel fasteners
- ISO 5211 mounting standard
- If necessary, all packages are direct mount if possible, or supplied with carbon steel bracket and coupler.



Double Acting

Available 2” through 12”

Cycle time 12-15 second

Available double acting, for on/off service

Option: 4-20mA control for modulating service

Spring return option available -
call for pricing

Worm gear type, brake not required

SIZE	LUG STYLE	WAFFER STYLE	VOLTAGE	ON/OFF
2	BFL02EW110	BFW02EW110	120/60/1	ON/OFF
2.5	BFL25EW110	BFW25EW110	120/60/1	ON/OFF
3	BFL03EW110	BFW03EW110	120/60/1	ON/OFF
4	BFL04EW110	BFW04EW110	120/60/1	ON/OFF
5	BFL05EW110	BFW05EW110	120/60/1	ON/OFF
6	BFL06EW110	BFW06EW110	120/60/1	ON/OFF
8	BFL08EW110	BFW08EW110	120/60/1	ON/OFF
10	BFL10EW110	BFW10EW110	120/60/1	ON/OFF
12	BFL12EW110	BFW12EW110	120/60/1	ON/OFF

Above with standard double acting actuators and butterfly valve with EPDM seats. Consult factory for other options, voltages, and spring return assemblies.

JOB NAME _____
LOCATION _____

CONTRACTOR _____
CONTRACTOR P.O. NO. _____

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____