



GLOBE STYLE CIRCUIT BALANCING VALVES

Model #	List Price	Size / Inches	End Connection	Shipping Weight
GS 050	\$175	1/2"	Threaded	2
GS 075	\$200	3/4"	Threaded	2
GS 100	\$260	1"	Threaded	2
GS 125	\$380	1.25"	Threaded	3
GS 150	\$460	1.5"	Threaded	4
GS 200	\$685	2"	Threaded	6
GS 250	\$1,695	2.5"	Flanged	31
GS 300	\$2,570	3"	Flanged	44
GS 400	\$3,540	4"	Flanged	57
GS 500	\$6,310	5"	Flanged	88
GS 600	\$8,075	6"	Flanged	110
GS 800	\$13,875	8"	Flanged	282

Notes:

- (1) 1/2" Through 2" Valves - Maximum Working Pressure 290 PSI
- 1/2" Through 2" Valves - Maximum Operating Temperature -22° to 250° F
- 2" Through 6" Valves - Maximum Working Pressure 225 PSI
- 2" Through 6" Valves - Maximum Operating Temperature 14° to 250° F
- (2) P/T Plugs will be furnished on the valves. Schraders upon request.

ACCESSORIES:

*Model W820 readout meter 2.5" dial, plastic carrying case, two 5' hose, ± 2 to 3% full scale accuracy, dial range 0-60' H2O, 12 lb shipping weight.
 List Price: \$1,575.00

* Model W821 dual readout meter, two 2.5" dials, plastic carrying case, ± 2 to 3% full scale accuracy, one gauge 0 - 135" and other 0 - 60' complete with two 5" hoses, 14 pound shipping weight.
 List Price: \$2,632.00